COR VISION EVOLUTION

SYSTEM



Sightlines

Frame 160 mm / 248 mm 3 rail / 336 mm 4 rails

Lateral sightline 62 mm

Interlock 25 mm

Glazing

Max. 44 mm, Min. 28 mm

Maximum sash dimensions

Width (L) 3,500 mm, Height (H) 3,500 mm

Maximum sash weight

500 kg

Consult maximum weight and dimensions according to typologies



COR VISION EVOLUTION SYSTEM

APA FACADE SYSTEMS

The new version of the Cor Vision accentuates its minimalism thanks to a closing system that allows the sashes to be fully hidden within the frame, opening up to infinite views that are only interrupted by a 25 mm interlock.

- High thermal & acoustic performance
- Up to 3.5 x 3.5 m/sash
- 25 mm interlock
- Hidden track possibility





FEATURES

U-value	Uw ≥ 0.88 (W/m²K)
Acoustic insulation	Rw up to 43 dB
Air permeability	Class 4
Watertightness	Class E900
Wind resistance	Class C3


Reference test 4.00 x 3.038 m / 2 sashes




NEW HANDLE

The handle is conceived to achieve total concealment of the sashes behind the frame, activating the opening and closing manoeuvre with a smooth semicircular turn.


DOUBLE TRACK




DRAINAGE SOLUTION




INTERLOCK




REINFORCED INTERLOCK



BI-PART OPENING



OPEN CORNER



OPENING POSSIBILITIES

Sliding

Possibility of 1, 2, 3 and 4 rails

Possibility of inner and outer corner sash at 90° without mullion

Pocket possibility

